



TEGERA® 8106

Leather glove, 0,65-0,8 mm full grain goatskin of top quality, Cat. II, black, water repellent leather, hook-and-loop, for allround work

PROPERTIES

High level of protection, extremely good fingertip sensitivity, extra flexible, very durable, perfect fit

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,65-0,8 mm

DEXTERITY 5

FASTENING Hook-and-loop

LENGTH RANGE 230-255 mm

COLOUR Black

PAIRS PER PACKAGE/CARTON 3/60

PIECES PER BOX 0

DISPLAY Thread OUTER MATERIAL SPECIFICATION Leather, natural latex

SIZE	ART. NO.	EAN NO.
6	8106-6	7340118331386
7	8106-7	7340118331478
8	8106-8	7340118331560
9	8106-9	7340118331652
10	8106-10	7340118331744
11	8106-11	7340118331836
12	8106-12	7340118331928

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 8106

FEATURES

Water repellent

PREVENTS RISK OF

Blisters, grazes, scratches, lacerations, contact with dirt, contact with damp

PRIMARY ENVIRONMENTS OF USE

Moist environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Security- and police work

PRIMARY INDUSTRIES OF USE

Service

TYPE OF WORK

Medium weight

2(3)

CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016 EN ISO 11640:2012
2011X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8106

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	0	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016 EN ISO 11640:2012
2011X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com